



Product Service

CERTIFICATE

No. Z1A 09 01 66779 003

Holder of Certificate: Govaerts Recycling nv

Kolmenstraat 1324
3570 Alken
BELGIUM

Certification Mark:



Product: Fall protection slabs

The product meets the requirements of the German Equipment and Product Safety Act. The Certification marks shown above can be affixed on the product. The certification marks must not be altered in any way. The use of the GS-Mark is permitted until the listed date, the use of the TÜV-Mark is unlimited, unless it is cancelled. See also notes overleaf.

Test report no.: 71333568-6

GS-Mark valid until: 2014-01-21

Date, 2009-01-21

Page 1 of 2



**CERTIFICATE****No. Z1A 09 01 66779 003****Model(s):**

Rubber granulate slabs Govaflex 30 mm
Rubber granulate slabs Govaflex Universal Tile 30 mm
Rubber granulate slabs Govaflex 40 mm
Rubber granulate slabs Govaflex 50 mm
Rubber granulate slabs Govaflex 70 mm
Rubber granulate slabs Govaflex 80 mm
Govaflex Elastic Pavement Blocks

Parameters:

Govaflex articles consist of black rubber granulate and coloured binding material.
The Govaflex articles have shock absorbing properties.

Govaflex 30:

Dimensions: 500 x 500 x 30 mm
Weight: approx. 20,8 kg/m²
Max. fall height: 1,0 m

Govaflex Universal Tile:

Dimensions: 400 x 400 x 30 mm
Weight: approx. 20,8 kg/m²
Max. fall height: 1,0 m

Govaflex 40:

Dimensions: 500 x 500 x 40 mm
Dimensions: 1000 x 500 x 40 mm
Weight: approx. 26,0 kg/m²
Max. fall height: 1,2 m

Govaflex 50:

Dimensions: 500 x 500 x 50 mm
Dimensions: 1000 x 500 x 50 mm
Weight: approx. 30,0 kg/m²
Max. fall height: 1,5 m

Govaflex 70:

Dimensions: 500 x 500 x 70 mm
Weight: approx. 41,6 kg/m²
Max. fall height: 2,1 m

Govaflex 80:

Dimensions: 500 x 500 x 80 mm
Weight: approx. 48,0 kg/m²
Max. fall height: 2,4 m

Govaflex Elastik Pavement Blocks:

Dimensions full block: 200 x 165 x 43 mm
Weight: approx. 38,0 kg/m²

Tested according to:

DIN EN 1177:2008; EN 1177:2008

Factory(ies):

37208

Main-Certificate no.:

Z1A 09 01 37208 012

